



ELECTRIC SPEC :

- 1. IMPEDANCE : 75 OHM
- 2. V.S.W.R. : 0-2 GHZ LESS THEN 1.15
- 3. RETURN LOSS : 0-3GHZ LESS THEN -25db
- 4. INSERTION LOSS : 0-3 GHZ LESS THEN -0.3db

NOTE : MATERIAL & FINISH

- 1.SHELL : BRASS / GOLD
- 2.BODY : BRASS / GOLD
- 3.INSULATION:DELTRIN / NATURE
- 4.GRASET : SILICON / ORANGE
- 5.WASHER : IRON / NICKEL
- 6.SPRING : K10 STEEL / NICKEL
- 7.WASHER : IRON / NICKEL
- 8.PIN: BRASS / GOLD

NOTE : MATERIAL & FINISH

- 9.INSULATION : P.E. / NATURE
- 10.BODY : BRASS / GOLD
- 11.CONTACT : BRASS / NICKEL
- 12.RING : DELRIN / NATURE
- 13.BODY : BRASS / BLACK NICKEL
- 14.CONTACT:BRASS / GOLD
- 15.INSULATION:TEFLON / NATURE
- 16.FUNCTION COLOR BAND:
P.E. / ANY COLOR

THIRD ANGLE	UNIT	DATE
	MM	DATE
SCALE	APPROVED BY	DRAWING BY
	HARRISON	JACK

BNC MALE COMPRESSION CONNECTOR FOR RGB CABLE
DRAWING NO. BC99G-G1V10



Structured Cable Products
Quality Installations Deserve Quality Products

6228 HIATUS ROAD, TAMARAC, FL 33321
(954) 327-5770 (954) 327-8176 www.scpcat5e.com