SCP Structured Cable Products
Quality Installations Deserve Quality Products

www.scpcat5e.com

SCP Part Number: RG6/UDC-WT

REV.A

Cross Section



Description

RG6/U HDTV SERIAL DIGITAL COAX 3.0 GHz- 18 AWG BC, 100% AL FOIL, 95% TC BRAID,CLEAR PVC JKT- WHITE - 500 FT REEL IN BOX

Marking

STRUCTURED CABLE PRODUCTS EXXXXXX (UL) OR C(UL) CM 18 AWG BC 75C MM/YY -- P/N: RG6/UDC -- RG6/U HDTV SERIAL DIGITAL COAX SWEEP TESTED TO 3.0 GHz, 100% AL FOIL, 95% TC BRAID CE EU RoHS EC ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 xxxxFEET

Construction

Center Conductor:	**Bare Copper**
Size	18AWG
Dia.(in/mm)	0.0403/1.02
Insulate	**Skin Foam PE**
Nom. Thickness(in/mm)	0.070/1.78
Insulation Dia.(in/mm)	0.180/4.57
Shield	**Bonded Aluminum foil**
Coverage area (%)	100
Braid Shield	**Tinned Copper**
Coverage area (%)	95
Jacket	**Clear PVC**
Nom. Thickness(in/mm)	0.030/0.76
Min. Thickness(in/mm)	0.024/0.61
Cable Dia.(in/mm)	0.272/6.91
Packing	**Reel in box**
Length(ft/m)	500/152.5
Gross Weight(lbs/kg)	24.47/11.1

Performance

Electrical Characteristics:[@68°F.(20℃.)]

Frequency (MHz)	Attenuation (dB/100ft)	Attenuation (dB/100m)
5	0.52	1.71
50	1.47	4.82
100	2.05	6.73
200	2.84	9.32
400	4.06	13.32
700	5.60	18.37
900	6.24	20.47
1000	6.60	21.65
1450	8.04	26.38
1800	8.84	29.00
2200	9.77	32.05
2500	11.13	36.52
2750	11.58	37.99
3000	12.06	39.57

Dielectric Strength (kV/min)		1
Impedence (ohms)		75±3.0
SRL (dB)	5~1000MHz	>=23
	1001~3000MHz	>=20
Capacitance (pF/ft)		16.2
Conductor DCR@ 20°C (ohms/kft)		6.55
DC Loop Resistance@ 20°C (ohms/kft)		10.68
Velocity Of Propagation (%)		85

Mechanical Characteristics:

Test Object:			Jacket
Test Material			
Before	Tensile strength	(psi)	>=2000
Aging	Elongation	(%)	200
Aging Condition		(℃_hrs)	100_168
After	Tensile strength	(%)	>=85%unaged
Aging	Elongation	(%)	>=50%unaged
Cold Bend		(-20±2°C/4hrs)	No crack
Jacket Longitudinal Shrinkage		(%)	>=5
Center Conductor break Strength		(lbs)	85
Operating Temperature Range		(℃)	-20~75

Standards

UL, CE, RoHS

Rev Date: 05/2013