



# Structured Cable Products

Quality Installations Deserve Quality Products

Web:www.scpcat5e.com  
Email:sales@scpcat5e.com

## SPECIFICATION SHEET

22-Apr-2014

Product Number : 14/2FPLP-GN

**RoHS**

Description : 2C/14 AWG SOLID FPLP PLENUM **GREEN**- 1000 FT SPOOL

Conductor : 14 AWG Solid SBC Conductor	
Total Cable Weight : 56 kg/km	Final Diameter : 0.206 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 2.6 Ohms / 1000 ft	Mutual Capacitance : 24.6 pF/ft
Impedance : 73.7 Ohms	
Velocity of Prop : 67 %	Inductance. : 1.2 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 14/2FPLP - - - (UL) CL2P/CL3P  
E198137 OR FPLP 75°C FT-6 UNSH 2/C 14 AWG SOLID --- ZONE/DEVICE A  
B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.142	NEC Articles: 760 FPLP
Ins Thickness: 0.011	Min. Bend Radius/Minor Axis: 1.442 inches
Jkt Thickness: 0.017	Operating Temperature : -20°C to 75°C
Certified: UL CL2P/CL3P OR FPLP	Standard UL Temp : 60°C
Flame Rating: FT-6	
Max Voltage: 300V	

Package Weight: 37.50 lbs / 17.05 kgs

( All of the above values are approximated to within +/- 10% )