

SPECIFICATION SHEET

web: www.scp5e.com
email: sales@scp5e.com

7-Aug-2014

Product Number : 14/4FPLP

RoHS

Description : 4C/14 AWG SOLID FPLP PLENUM - 1000 FT SPOOL

Conductor : 14 AWG Solid SBC Conductor	
Total Cable Weight : 104 kg/km	Final Diameter : 0.242 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 2.6 Ohms / 1000 ft	Mutual Capacitance : 29.9 pF/ft
Impedance : 62.8 Ohms	
Velocity of Prop : 65 %	Inductance. : 1.3 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 14/4FPLP - - - (UL) CL2P/CL3P
E198137 OR FPLP 75°C FT-6 UNSH 4/C 14 AWG SOLID --- ZONE/DEVICE A
B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.201

Ins Thickness: 0.011

Jkt Thickness: 0.017

Certified: UL CL2P/CL3P OR FPLP

Flame Rating: FT-6

Max Voltage: 300V

(All of the above values are approximated to within +/- 10%)

7201404BPV6.03S.1000