

SPECIFICATION SHEET

www.scpcat5e.com
sales@scpcat5e.com

14-May-2014

Product Number : 16/4FPLR-SH

RoHS

Description : 4C/16 AWG SOLID FPLR SHIELDED PVC- RED- 1000 FT SPOOL

Conductor : 16 AWG Solid SBC Cond.	
Total Cable Weight : 73 kg/km	Final Diameter : 0.201 inches
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 4.12 Ohms / 1000 ft	Mutual Capacitance : 21.87 pF/ft
Impedance : 75.42 Ohms	
Velocity of Prop : 66.2 %	Inductance. : 1.37 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 16/4FPLR-SH -RISER FIRE
ALARM CABLE (UL) CL2R/CL3R E198137 OR FPLR (UL) C(UL) CMG CMR
SH 4/C 16 AWG SOLID PVC JKT --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6
7 8 9 RoHS

Cabled OD Avg: 0.164	NEC Articles: 760 FPLR
Ins Thickness: 0.010	Shield: AL FOIL
Jkt Thickness: 0.015	Min. Bend Radius/Minor Axis: 1.407 inches
Certified: UL CL2R/CL3R OR FPLR/CMG/CMR	Operating Temperature: -20°C to 60°C
Flame Rating: Riser	Standard UL Temp: 60°C
Max Voltage: 300V	

(All of the above values are approximated to within +/- 10%)