



MATERIAL

PLASTIC HOUSING : ABS high-impact UL94V-0 thermoplastic
 INSERT:Brass 3604 surface gold plating

PHYSICAL CHARACTERISTICS

OPERATING TEMPERATURE RANGE : -10°C TO 60°C
 STORAGE TEMPERATURE RANGE : -40°C TO 68°C
 HUMIDITY : 10%~90%RH

ELECTRICAL

IMPEDANCE: 75 ohm
 FREQUENCY RANGE: 0~3 GHz
 WORKING VOLTAGE: 250 VRMS max.
 DIELECTRIC WITHSTANDING VOLTAGE: 500VRMS min.
 VSWR: 1.35 max
 CONTACT RESISTANCE: 1.Center Contact: 5 Milliohms Max.
 2.Outer Contact: 1 Milliohms Max.
 INSULATOR RESISTANCE: 1000 Megohms min.

Colors Available: Light Almond & White

Scale	1.5:1	All Copy Rights Reserved	
3rd Angle Projection		SPEAKER BINDING POST KEYSTONE INSERT, GOLD-PLATED	
Unit	mm	SCP P/N	241BK-XX
Date	2015-09-16		
Tolerance			
~20	~50	~150	150~ ANGLE
±0.2	±0.4	±0.5	±2°
Drawn by		Checked by	
FHL		Santiago	